PATENT COOPERATION TREAT

PCT

HEC'D	40	UUI	ZUUS
WIPO		*************	PCT

INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

(Chapter II of the Patent Cooperation Treaty)

(PCT Article 36 and Rule 70)

Applicants or an in the							
Applicant's or agent's file reference 758.1509WOU1	FOR FURTHER	PR FURTHER ACTION See Form PCT/IPEA/416					
International application No. International filir PCT/US2004/018536 10.06.2004		ate (day/month/year)	Priority date (day/month/year) 12.06.2003				
International Patent Classification (IPC) or national classification and IPC F01N3/035, F01N3/025, F01N3/08							
Applicant DONALDSON COMPANY, INC. et al.							
	 This report is the International preliminary examination report, established by this International Preliminary Examining Authority under Article 35 and transmitted to the applicant according to Article 36. 						
2. This REPORT consists of a	a total of 5 sheets, includin	g this cover sheet.					
3. This report is also accompa	anied by ANNEXES, comp	rising:					
a. 🗆 sent to the applican	t and to the International B	ureau) a total of sheets a	s follows:				
and/or sheets of the de	 a. sent to the applicant and to the International Bureau) a total of sheets, as follows: sheets of the description, claims and/or drawings which have been amended and are the basis of this report and/or sheets containing rectifications authorized by this Authority (see Rule 70.16 and Section 607 of the Administrative Instructions). 						
sheets which supersede earlier sheets, but which this Authority considers contain an amendment that goes beyond the disclosure in the international application as filed, as indicated in item 4 of Box No. I and the							
b. (sent to the International Bureau only) a total of (indicate type and number of electronic carrier(s)), containing a sequence listing and/or tables related thereto, in computer readable form only, as indicated in the Supplemental Box Relating to Sequence Listing (see Section 802 of the Administrative Instructions).							
4. This report contains indicat	ions relating to the following	items:					
-	he opinion	g Korris.					
☐ Box No. II Priority	ne opinion						
	hlishment of oninion with re	and to					
□ 	nity of invention	gard to novelty, inventive s	step and industrial applicability				
☑ Box No. V Reasone applicabil	======================================						
☐ Box No. VI Certain de	ocuments cited						
⊠ Box No. VII Certain de	efects in the international a	pplication					
☐ Box No. VIII Certain ol	oservations on the internati	onal application					
Date of submission of the demand		Date of completion of this					
		Sate of completion of this	тероп				
22.04.2005		27.10.2005					
Name and mailing address of the international preliminary examining authority:		Authorized Officer	Authorized Officer				
European Patent Office - P.B. 5818 Patentiaan 2 NL-2280 HV Rijswljk - Pays Bas Tel. +31 70 340 - 2040 Tx: 31 651 epo ni Fax: +31 70 340 - 3016		Louchet, N					
	•	Telephone No. +31 70 34	0-4212				

INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

International application No. PCT/US2004/018536

_	D 11					
_	Box No. I	Basis of the report				
1.	With regard filed, unless	regard to the language , this report is based on the international application in the language in which it wa unless otherwise indicated under this item.				
	which □ inte □ pub	 This report is based on translations from the original language into the following language, which is the language of a translation furnished for the purposes of: □ international search (under Rules 12.3 and 23.1(b)) □ publication of the international application (under Rule 12.4) □ international preliminary examination (under Rules 55.2 and/or 55.3) 				
2.	With regard to the elements * of the international application, this report is based on (replacement sheets which have been furnished to the receiving Office in response to an invitation under Article 14 are referred to in this report as "originally filed" and are not annexed to this report):					
	Description	, Pages				
	1-17	as originally filed				
	Claims, Nur	nbers				
1-9 10-16		as originally filed				
		as amended (together with any statement) under Art. 19 PCT				
	17-26	filed with telefax on 22.04.2005				
	Drawings, S	heets				
	1/6-6/6	as originally filed				
	□ a sequ	ence listing and/or any related table(s) - see Supplemental Box Relating to Sequence Listing				
3.	☐ the ☐ the ☐ the ☐ the	the description, pages the claims, Nos. the drawings, sheets/figs the sequence listing (specify):				
4.	Supplement the the the the the the the the the th	port has been established as if (some of) the amendments annexed to this report and listed below an made, since they have been considered to go beyond the disclosure as filed, as indicated in the tal Box (Rule 70.2(c)). description, pages claims, Nos. drawings, sheets/ligs sequence listing (specify): table(s) related to sequence listing (specify):				
	* If it	em 4 applies, some or all of these sheets may be marked "superseded."				

INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

International application No. PCT/US2004/018536

Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial Box No. V applicability; citations and explanations supporting such statement

1. Statement

Novelty (N)

Yes: Claims

4-9, 12-14, 16, 17, 18, 20, 21, 25, 26

Claims No:

1-3, 10, 11, 15, 19, 22-24,

Inventive step (IS)

Yes: Claims

Claims

No: Claims 1-4, 626

Industrial applicability (IA)

Yes: Claims

No:

1-26

2. Citations and explanations (Rule 70.7):

see separate sheet

Box No. VII Certain defects in the international application

The following defects in the form or contents of the international application have been noted:

see separate sheet

PCT/US2004/018536

Item V.

1.1. Document US 6 487 852 (D1) discloses (see column 1, line 7 - column 3, line 18; figure 1):

a method for injecting fuel into a transient exhaust stream (12) of an exhaust system (10), the method comprising:

selecting a control volume within the exhaust system; and using a model derived from a transient energy balance equation for the control volume to determining the rate for fuel to be dispensed into the exhaust stream (12).

Therefore, the present application does not meet the criteria of Article 33(1) PCT, because the subject-matter of claims 1 is not new in the sense of Article 33(2) PCT.

1.2. Document EP 1 149 991 (D3) discloses (see § [001]-[012]; figures 1-3):
An exhaust system comprising:
an exhaust conduit (90);
a fuel injection nozzle (110) positionned into the exhaust conduit (90);
an air line for supplying air to the nozzle (114);
a fuel line (106 for supplying fuel to the nozzle (114); and
a controller (120) for determining a rate of fuel to be injected into the exhaust conduit.

Therefore, the present application does not meet the criteria of Article 33(1) PCT, because the subject-matter of claim 10 is not new in the sense of Article 33(2) PCT.

2.1. Dependent claims 2-4, 6-9 and 11-26 do not appear to contain any additional features which, in combination with the features of any claim to which they refer, meet the requirements of the PCT with respect to novelty or inventive step, because the subject-matter of claims 2, 3 are already known from EP 1 273 773 (D4) (see § [021]-[071]; figure 1), the features of claims 11, 15, 19, 22-24 are known from D3, the features of claims 7-9 are known from US 5 950422 (D5) (see col. 2, line 3 - col. 7, line 16; figures 1-3) in combination with D2 and the features of claims 4, 6, 12-14, 16-18, 20, 21, 25 and 26 are a matter of design choice falling within the normal activity of the person skilled in

INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY (SEPARATE SHEET)

International application No.

PCT/US2004/018536

tl	h	_	2	rt
L1		-	~	

Item VII.

- 2.1. Independent claims 1 and 10 are not in the two-part form in accordance with Rule 6.3(b) PCT, which in the present case would be appropriate, with those features known in combination from the prior art being placed in the preamble (Rule 6.3(b)(I) PCT) and with the remaining features being included in the characterising part (Rule 6.3(b)(ii) PCT).
- 2.2. The features of the claims are not provided with reference signs placed in parentheses (Rule 6.2(b) PCT).
- 2.3. The units of pressure employed in claims 17-21 and on pages 13, 14 are not additionally expressed in terms of the units stipulated by Rule 10.1(a) PCT.

13:49

FROM-Marchant & Gould

6122329081

T-923 P.013/015 F-196

We claim:

1. A method for injecting fuel into a transient exhaust stream of an exhaust system, the method comprising:

selecting a control volume within the exhaust system; and
using a model derived from a transient energy balance equation for the
control volume to determining the rate for fuel to be dispensed into the exhaust
stream.

- 2. The method of claim 1, wherein the control volume includes a catalytic converter, wherein the catalytic converter is positioned upstream from a diesel particulate filter, wherein the fuel is dispensed upstream of the catalytic converter, and wherein rate for dispensing the fuel is selected to achieve a temperature at a downstream end of the catalytic converter that is suitable for causing regeneration of the diesel particulate filter without causing the diesel particulate filter to overheat.
- 3. The method of claim 1, wherein the exhaust system includes a catalytic converter positioned upstream from a diesel particulate filter and a fuel dispensing nozzle positioned upstream from the catalytic converter, and wherein the control volume starts upstream from the fuel dispensing nozzle and ends at the downstream end of the catalytic converter.
- 4. The method of claim 1, further comprising accessing pressure, temperature and mass flow data for the exhaust system, and using the data in concert with the model to determine the rate of fuel to be injected.
- 5. The method of claim 1, wherein the exhaust system includes a catalytic converter positioned upstream from a diesel particulate filter and a fuel injector positioned upstream from the catalytic converter, wherein temperature and pressure data are sensed upstream of the fuel injector and downstream of the catalytic converter, and wherein the temperature and pressure data are used in concert with the model to determine a fuel injection rate suitable to reach a temperature at the downstream end of the catalytic converter that is within a target temperature range.

13:50

FROM-Merchant & Gould

6123329081

T-923 P.014/015 F-196

- 6. The method of claim 2, wherein the model takes into consideration the vaporization efficiency of the fuel.
- 7. The method of claim 2, wherein the model takes into consideration the fuel conversion efficiency of the catalytic converter.
- 8. The method of claim 2, wherein the model takes into consideration the thermal energy storage rate of the catalytic converter.
- 9. The method of claim 2, wherein the model takes into consideration mass flow through the control volume.
- 10. An exhaust system comprising:
 an exhaust conduit;
 a fuel injection nozzle for injecting fuel into the exhaust conduit;
 an air line for supplying air to the nozzle;
 a fuel line for supplying fuel to the nozzle; and
 a controller for determining a rate of fuel to be injected into the exhaust
- 11. The exhaust system of claim 10, further comprising a pre-mix region in which the air and fuel are mixed prior to reaching the nozzle.

conduit.

- 12. The exhaust system of claim 10, wherein the air and fuel are mixed at the nozzle.
- 13. The exhaust system of claim 1, further comprising a catalytic converter and a diesel particulate filter positioned within the exhaust conduit, the catalytic converter being positioned upstream of the diesel particulate filter and the nozzle being positioned upstream from the catalytic converter.
- 14. The exhaust system of claim 13, wherein the controller controls a rate of fuel injected into the exhaust conduit by the fuel injection nozzle to reach a temperature at the diesel particulate filter suitable for causing regeneration.

19

13:50

FROM-Merchant & Gould

6123329081

T-923 P.015/015 F-186

- 15. The exhaust system of claim 10, wherein the nozzle is positioned upstream from a lean NOx catalyst.
- 16. The exhaust system of claim 10, wherein the nozzle is positioned upstream from a NOx absorber.

